

IJETSR www.ijetsr.com ISSN 2394 – 3386 Volume 4, Issue 8 August 2017

Enrichment in Safety System by Utilization of Safety seat belt in Automobile Vehicle System

Prof. Manish D.Patel*, Prof. Rajesh V. Chaudhari*, Prof. Vinod P.Rajput*, Prof. Jayendra B.Patel*

* Assistant Professor in Mechanical Engineering

Department at Smt.S.R.Patel Engineering College, Dabhi-Unjha,North Gujarat, India.

ABSTRACT

We all are using and entertain with driving vehicles. Vehicles are manufactured under the strict government rules and relations by various manufactures. Manufacturer always provided safety features but some time we, users ignore the safety importance and not follow the purpose of safety system intentionally or by mistake. There are certain safety and security concern about which you must aware while driving an automobile vehicle out of them one of them is safety belt. Here in this paper attempt is towards utilization of safety belt system to enrich safety of vehicals user.

Keywords: Human error, Safety belt, Vehicle design, Sensor, Limit switch, Push switch.

INTRODUCTION

Vehicle safety is concern with the safety system for all riders and presently helpful to minimize crashing of vehicles which finally reduce human injuries in the case of vehicle accident. Substantial and evidence-based improvements have been made in the last 15 years and Research has identified large scope for enriching vehicle safety [1]. The European Commission has recommended that if all car manufacturer are designed their vehicles and provide the safety equipments as normally find in high class vehicles, majorities of accidents can be avoided [2].

We actually find numbers of human injuries during the accident of automobile vehicle but they can minimize by utilization of proper safety aids provided by manufacturers. Users are many time ignore the safety system and due to that after the accidents they have to pay a lot.

SEAT BELT SAFETY SYSTEM

All the manufactures are provided seat belt system for the safety of rider. We know that most of riders are not wearing a seat belt during driving intentionally or due to human error. A seat belt safety system designed for present class vehicles are elements of a common electrical circuit operative to control the drive system and due to that in advance model of automobile vehicles visual as well as audio signal is provided if seat belt is not used [3]. But still this system is not related to vehicle engine operation. Even when occupied seat is not engaged in the seatbelt holder means user is not using provided safety belt system then also vehicle can operate.

Here we developed the system for wearing a seat in such a way that if rider doesn't wish to wear a safety seat belt vehicle will not start ignition. This system forced to rider to wear a safety belt. One more thing enrich this system is regarding radio or tape operating system. If rider doesn't wish to wear a seat belt he or she will not entertain with radio or tape.

www.ijetsr.com ISSN 2394 – 3386 Volume 4, Issue 8 August 2017

WORKING DESIGN AND INSTALLATIONOF SAFETY SYSTEM

Micro limit switch is fitted in the seat belt connecter (seat belt holder) at calculated seat belt angle as shown in figure:1. The limit switch is connected with Ardiuno circuit with cables as shown in figure:3.






Fig.1 Seat belt angle

Fig.2 Fitted limit switch in seat holder




Fig.3 Circuit diagram



www.ijetsr.com ISSN 2394 - 3386

Volume 4, Issue 8

August 2017





Fig.4 LCD

Fig.5 Controller

Power supply to the engine and tape is provided through relay controller, so engine or tape will not strart untill seat belt is in enggage condition. Small LCD screen is also fitted on controller for identification of problem why engine or tape is not started? This will be helpful for new operator of vehicle who is not aware about modified safety system. If seat belt is not engagged the massage 'safety belt open' will display on that screen.

CONCLUSION

The modified developed safety seat belt system is very much helpful for minimise human injuries during accident and reduce human errors. This developed safety seat belt system is affordable and can easily fitted in any automobile vehicle.

REFERENCES

- [1] Aga, M. and Okada, A. 2003. Analysis of Vehicle Stability Control (VSC)'s effectiveness from crash data. ESV Paper 541, 18th ESV Conference, Nagoya
- [2] Allsop, R.E. ed 1999. European Transport Safety Council, Safety of pedestrians and cyclists in urban areas, Brussels
- [3] Ashton, S.J., Mackay, G.M. 1983. Benefits from changes in vehicle interior design. In: Proceedings of the Society of Automotive Engineers. Detroit, MI, Society of Automotive Engineers, 255 –264 (Publication No.121)