
Spectral Characteristics of Mechanically Induced of Ultralong Period Fiber Gratings (ULPFG) as a Pressure Sensor.

V. Mishra, V V Dwivedi

C.U shah University, Surendranagar, Gujrat

Abstract. We report here for the fabrication and characterization of mechanically induced ultralong period fiber gratings (MULPFG) with period size up to several millimeters.

In these gratings we studied the spectral characteristic of LPFG and ULPFG.

Index Terms: MULPFG, reversible grating, pressure sensing.

1 Introduction

The optical fiber grating is one of the key elements in the established and emerging fields of optical communication systems. Fiber grating is an infiber spectrally selective component and have low losses, high stability, and small size compatible with fiber sizes and low cost. Their applications also spread into the area of optical fiber sensing.

Long period fiber grating (LPFG) is the special case of FBG. It was first suggested by Vengsarkar and coworkers in 1996. Their spectral properties i. e. resonance wavelength, bandwidth etc. can be varied in a wide range. All these features make LPFG as an important component in a variety of light wave applications such as band rejection filter[1], wavelength selective attenuator, dispersion compensator, multichannel filters in WDM applications and gain flatteners for Erbium doped fiber amplifiers[2]. These gratings are also very suitable for various sensing applications. Sharp filtering characteristics, ease of fabrication, direct connectivity to fiber, high sensitivity to external parameters, and easiness in adjusting the resonant wavelength by simply adjusting the grating period are the strong points to push towards the detail study of this device. The period of a typical long period fiber grating (LPFG) ranges from 100 μ m to 1000 μ m.

The LPFGs with periods exceeding one millimeter are called ultralong period fiber gratings (ULPFG). The long period size makes fabrication of ULPFG very easy as well as cheap.

ULPFG can be induced optically or mechanically [3] - [5]. Optically induced gratings are permanent, whereas mechanically induced gratings are reversible.

Xuwen Shu et. al. reported fabrication and characterization of ULPFG for the first time in 2002 by using point-by-point writing technique with 244nm UV beam from a frequency doubled Argon ion laser [3]. An ultralong period fiber grating with periodic groove structure(G-ULPFG) fabricated by using an edge-written method with high-frequency CO₂ laser pulses is reported by Tao Zhu and co-workers in 2009[4].

We report here, for the first time to our knowledge, the fabrication and characterization of mechanically induced ULPFGs (MULPFG) with periods up to several millimeters. Mechanically induced long period fiber gratings (MLPFG) and MULPFG induced by pressure need neither a special fiber nor an expensive writing device for fabrication. These gratings also offer advantages of being simple, inexpensive, erasable, and reconfigurable and also gives flexible control of transmission spectrum,

2 Theory

ULPFG is a special case of LPFG. In LPFG the core LP₀₁ mode is coupled with cladding modes having same symmetry, namely LP_{0m} modes [6]. Whereas in ULPFG the coupling of the fundamental guided core mode to

the cladding modes of high diffraction orders takes place [7]. The phase matching condition for a high diffraction order grating is given by (1).

$$\frac{cl}{co} = m \lambda_{res} \quad (1)$$

$$\lambda_{res} = \frac{d}{N(n_{eff}^{co} - n_{eff}^{cl,m})}$$

Where λ_{res} is the resonant wavelength, n_{eff}^{co} and $n_{eff}^{cl,m}$ are effective indexes of

fundamental core mode and m^{th} cladding mode of N^{th} diffraction order respectively. d is the grating period and N is the diffraction order. $N=1$ for LPFG.


The resonant wavelength with the variation in the effective indexes of the core and cladding ignoring the dispersion effect is given by (2).

$$\lambda'_{res} = \frac{d}{N(n_{eff}^{co} - n_{eff}^{cl,m})} \times \left[1 + \frac{d}{2} \left(\frac{1}{co} \frac{d}{cl} \right) \right] \quad (2)$$

Where λ'_{res} is the resonant wavelength with variation in the effective indexes of core and cladding, n_{eff}^{co} and $n_{eff}^{cl,m}$ are the effective index changes of the fundamental core mode and m^{th} cladding mode of the N^{th} diffraction order.


3 Experiment


Reversible MLPFG and MULPFG of different periods ranging from several hundred microns to several millimeters were induced and characterized.





Experimental result:





Conclusion and Result:

As compared to reversible LPFG and ULPFG in single mode fiber (SMF28), these gratings have more number of transmission dips in the spectral response.

Resonant loss peaks with strengths of up to ~5 dB have been generated in the LPFG and ULPFG in multimode fiber.

The reversible LPFG and ULPFG induced in single mode fiber and multimode fibers are compared. It is found that single mode gratings gave better response (resonant loss peaks of up to ~7dB) as compared to multimode gratings (resonant loss peaks of up to ~5dB). But Multimode fiber has its own advantages because of large core diameter. Thus to combine the advantages of both single mode fiber and multimode fiber, a novel MSM structure is prepared to induce the reversible LPFG and ULPFG. The induced gratings are characterized and following conclusions are drawn:

Reversible LPFG in MSM structure gives single transmission dip, thus providing extremely wide tunable range without worrying about overlap among different bands in sensing application.

Resonant loss peak strength is around 17-18dB, which is much greater than maximum loss of 8dB in Single mode reversible LPFG and 5dB in multimode reversible LPFG.

References

- [1] Kenneth O. Hill and Gerald Meltz, "Fiber Bragg Grating Technology Fundamentals and Overview "Journal of Light wave Technology, Vol. 15, No. 8, August 1997.
- [2] Yanyu Zhao and Joseph C. Palais, " Fiber Bragg Grating Coherence Spectrum Modeling, Simulation, and Characteristics", Journal of lightwave technology, Vol. 15, No. 1, January 1997.

-
- [3] Ashish M. Vengsarkar, Paul J. Lemaire, Justin B. Judkins, Vikram Bhatia, Turan Erdogan, and John E. Sipe, “Long-Period Fiber Gratings as Band-Rejection Filters”, Reprint of most cited article from Journal of Lightwave Technology - Vol. 14, No. 1, pp 58-65, 1996.
- [4] T. W. MacDougall, S. Pilevar, C. W. Haggans, and M. A. Jackson, “Generalized expression for the growth of long period gratings,” IEEE Photon. Technol. Lett.,10 (10), pp. 1449-1451, 1998.
- [5] X. Shu, L. Zhang, and I. Bennion, “Sensitivity characteristics of long-period fiber gratings,” J. Lightwave Technol., 20(2), pp. 255-266 2002.
- [6] F. Y. M. Chan and K. S. Chiang, “Analysis of apodized phase-shifted long-period fiber gratings,” Opt.Commun., 244(1-6), pp. 233-243, 2005.
- [7] H. Ke, K. S. Chiang, and J. H. Peng, “Analysis of phase shifted long-period fiber gratings,” IEEE Photon.Technol. Lett., 10(11), pp. 1596-1598, 1998.
- [8] Jaikaran Singh, Dr. Anubhuti Khare, Dr. Sudhir Kumar, “Design of Gaussian Apodized Fiber Bragg Grating and its applications”, Jaikaran Singh et al. / International Journal of Engineering Science and Technology Vol. 2(5), 1419-1424, 2010.
- [9] Turan Erdogan:“Fiber Grating Spectra”, Journal of Light wave Technology, vol. 15, no. 8 August 1997.
- [10] K. O. Hill, Y. Fujii, D. C. Johnson, and B. S. Kawasaki, “Photosensitivity in optical fiber waveguides: Application to reflection filter fabrication,” Appl. Phys. Lett., vol. 32, pp. 647–649, 1978.